Safety Data Sheet (SDS)

Established Date: 01/Dec./2018 Revised Date: 01/Jun./2022

1. Identification of the Substance and of the Company Product Identifier:

Ceramic (include the coated or surface treated Ceramic)

Supplier Information:

Company Name: OSG Corporation

Address: 3-22 Honnogahara Toyokawa-City Aichi-Pref.

442-8543 Japan

Contact Department: Quality Assurance Dept. Phone Number: (536)25-1315 (International Dept.)

FAX Number: (536)25-1310

Emergency Phone Number: (536)25-1315

Recommended Use of the Ceramic

Cutting and drilling tools for metallic materials

Restrictions on Use of the Ceramic

Do not use for other than the specified purpose

Attention to the Phase/State of the Ceramic

- Ceramic as solid state like cutting tools is chemically stable and safe at explosive, flammable, combustible, pyrophoric, water-reactive, and oxidizability under normal environment.
- Ceramic is safe for use as the cutting tools (grinding, machining, rolling for metals) under normal condition.
- This SDS informs about the dust, fume or vapor which occur from Ceramic producing process such as raw material powder handling and grinding.

2. Hazard Identification

The GHS Classification

Some data (such as the burning rate test data, etc.) for the dust, fume or vapor which occur from Ceramic producing process are unavailable. Therefore, they are not be classified by GHS.

In here, GHS classification of the each metallic ingredients (cobalt, nickel and chromium) for composing the Ceramic can be disclosed. In addition, other hazards and harmful effects (for health, environment, physical and chemical) which are not listed are unclassifiable or non-applicable by GHS.

GHS classification for the hazards of cobalt alone in below, (When cobalt is included as ingredients of Ceramic.)

| Health Hazard | · Acute toxicity (oral) | Category4 |
|---------------|--|---------------|
| | • Acute toxicity (inhaled: dust, mist) | Category1 |
| | · Serious eye damage / eye irritation | Category2B |
| | Respiratory sensitization | Category1A |
| | · Skin sensitization | Category1A |
| | Carcinogenicity | Category2 |
| | Reproductive toxicity | Category1B |
| | Specific target organ toxicity | Category1 |
| | (Single exposure) | (Respiratory) |

| | • Specific target organ toxicity (Repeated exposure) | Category1 (Respiratory, Heart, Thyroid, Blood) |
|--------------------------|---|--|
| Environmental Hazard: | Hazardous to the aquatic environment – prolonged (Chronic hazard) Hazardous to the aquatic environment – repeated (Acute hazard) | Category1 Category1 |

GHS classification for the hazards of nickel alone in below,

(When nickel is included as ingredients of Ceramic.)

| (When mokel is meraded as ingredients of ceramic.) | | | |
|--|--|--------------------------------|--|
| Health Hazard | Respiratory sensitization | Category1 | |
| | · Skin sensitization | Category1 | |
| | · Carcinogenicity | Category2 | |
| | Specific target organ toxicity | Category1 | |
| | (Single exposure) | (Respiratory tract irritation) | |
| | Specific target organ toxicity | Category1 | |
| | (Repeated exposure) | (Respiratory) | |
| Environmental | Hazardous to the aquatic | Category4 | |
| Hazard: | environment – prolonged (Chronic | | |
| | hazard) | | |

GHS classification for the hazards of chromium alone in below, (When chromium is included as ingredients of Ceramic.)

| Health Hazard | · Serious eye damage | Category2B |
|---------------|--|--------------------------------|
| | · Respiratory sensitization | Category1 |
| | · Skin sensitization | Category1 |
| | · Germ cell mutagenicity | Category2 |
| | • Specific target organ toxicity | Category2 |
| | (Single exposure) | (Respiratory tract irritation) |
| | Specific target organ toxicity | Category3 |
| | (Repeated exposure) | (Respiratory) |

GHS Label Elements

GHS label elements of the each metallic ingredients (cobalt, nickel and chromium) for composing the Ceramic can be disclosed in below.

| | Cobalt | Nickel | Chromium | |
|------------------------|------------------------|------------------------|------------------------|--|
| Hazard Pictograms : | | | | |
| | | | | |
| Signal Words : | Danger | | | |
| Hazard | · Risk of causing | · Risk of causing | · Risk of causing | |
| Statements: | allergies, asthma or | allergies, asthma or | allergies, asthma or | |
| | breathing difficulties | breathing difficulties | breathing difficulties | |
| | if inhaled. | if inhaled. | if inhaled. | |

- Risk of causing an allergic skin reaction.
- · May cause cancer.
- May cause adverse effects on fertility or the unborn child.
- Risk of respiratory irritation.
- Cause of respiratory failure due to long-term or repetitive exposure.
- May be harmful to aquatic life due to long lasting effects

- Risk of causing an allergic skin reaction.
- · May cause cancer.
- Respiratory and kidney disorders
- Cause of respiratory failure due to longterm or repetitive exposure.
- May be harmful to aquatic life due to long lasting effects

- Risk of causing an allergic skin reaction.
- · Suspected of causing genetic

disease

- Failure to systemic toxicity
- Risk of respiratory irritation.

Precautionary Statements:

[Prevention]

- ·Obtain safety instructions* before use.
- ·Do not handle until all safety precautions have been read and understood.
- ·Use appropriate personal protection and ventilation system keeping away from exposure.
- ·Wear suitable protective gloves.
- ·When insufficient ventilation, wear respirator as required.
- ·Do not breathe dust, fume or vapor.
- ·Do not eat, drink or smoke in handling area.
- ·Wash skin thoroughly after handling.
- ·Do not release into the environment.

[Responses]

- · If inhaled, move to fresh air and take a rest with posture easy to breathe.
- ·If respiratory symptoms occurs, contact a doctor.
- ·When feeling ill, get medical advice/attention.
- ·Take off contaminated clothing and wash before reuse.
- \cdot If on skin, rinse away immediately with a large amount of water and soap.
- · If skin irritation occurs, contact a doctor and get medical advice/attention.
- · If exposed or concerned, get medical advice/attention.
- ·If dust is in eyes, immediately wash away with clean water (remove the contact lenses if possible). If irritation persists, get medical advice/attention.
- ·If a large amount of dust is swallowed, get medical advice/attention after ingesting plenty of water to dilute.

[Storage]

· Avoid sudden changes of temperature and high humidity for storage.

[Disposal]

· Dispose of contents/container to an approved waste disposal plant under the laws.

^{*}For safety instructions, refer to the Japan Cutting & Wear-resistant Tool Association website (http://www.jta-tool.jp/) .

3. Composition/Information on Ingredients

- Distinction between substance and mixture: Mixture
- Chemical name or general name: Ceramic
 - Ceramic may be coated or surface treated with the following substances.
 - AlCrN, AlN, Al₂O₃, (Al,Ti)N, B₄C, Cr₃C₂, CrN, MoS₂, Ti(B,C,N), TiC, TiCN, TiN, (Ti,Si)N, (Ti,Zr)N, WC

• Ingredients and concentration or concentration range (composition) of the Ceramic

| Ingredient | Chemical Formula | CAS No | Official Number of Law for PRTR | Official Number of Industrial Safety and Health Law | Composition mass% |
|--------------------------|---|------------|---------------------------------------|---|-------------------|
| Aluminum oxide | Al_2O_3 | 1344-28-1 | N/A | Appendix 9-189 | N/A |
| Zirconium oxide | $ m ZrO_2$ | 1314-23-4 | N/A | Appendix 9-313 | N/A |
| Titanium oxide | ${ m TiO_2}$ | 13463-67-7 | N/A | Appendix 9-191 | N/A |
| Ytterbium oxide | Yb_2O_3 | 1314-37-0 | N/A | N/A | N/A |
| Yttrium oxide | Y_2O_3 | 1314-36-9 | N/A | Appendix 9-54 | N/A |
| Erbium oxide | $\mathrm{Er}_{2}\mathrm{O}_{3}$ | 12033-89-5 | N/A | N/A | N/A |
| Magnesium oxide | MgO | 1309-48-4 | N/A | N/A | N/A |
| Chromium oxide | $\mathrm{Cr}_2\mathrm{O}_3$ | 1308-38-9 | Class 1:87 | Appendix 9-142 | N/A |
| Cerium oxide | CeO_2 | 1306-38-3 | N/A | N/A | N/A |
| Yttrium aluminum oxide | Y ₂ Al ₅ O ₃ | N/A | N/A | N/A | N/A |
| Silicon carbide | SiC | 409-21-2 | N/A | Appendix 9-336 | N/A |
| Aluminum nitride | AlN | 24304-00-5 | N/A | N/A | N/A |
| Silicon nitride | $\mathrm{Si}_{3}\mathrm{N}_{4}$ | 12033-89-5 | N/A | N/A | N/A |
| Titanium nitride | TiN | 25583-20-4 | N/A | N/A | N/A |
| Cobalt | Co | 7440-48-4 | Class 1:132 | A 1: 0.170 | N/A |
| Cobalt oxide | Co ₃ O ₄ | 1308-06-1 | Class 1:132 | Appendix 9-172 | N/A |
| Nickel | Ni | 7440-02-0 | Class 1:308 | A 1: 0.410 | N/A |
| Nickel oxide | NiO | 1313-99-1 | Class 1:309 | Appendix 9-418 | N/A |
| Tungsten Carbide | WC | 12070-12-1 | N/A | N/A | N/A |
| Tantalum carbide | TaC | 12070-06-3 | N/A | N/A | N/A |
| Niobium carbide | NbC | 12069-94-2 | N/A | N/A | N/A |
| Titanium carbide | TiC | 12070-08-5 | N/A | N/A | N/A |
| Titanium carbonitride | TiCN | N/A | N/A | N/A | N/A |

^{*}For the details regarding the content of the designated chemical material such as cobalt, nickel and chromium (effective digit: 2), please contact to the above supplier.

4. First-Aid Measures

If Inhaled

- If the high concentration of dust is inhaled or respiratory symptoms (coughs, gasping, shortness of breath, etc.) are experienced, move to fresh air and take a rest with posture easy to breathe. If breathing difficulties occur, administer oxygen inhalation. If breathing has stopped, immediately administer artificial respiration and get medical advice/attention.
- If irritation or rash persists, get medical advice and attention.

If on Skin

• If dust is contacted with skin, take off contaminated clothing and rinse the affected area with soapy water thoroughly. If irritation or rash persists, get medical advice/attention.

^{*}Even if the cemented carbide do not contain cobalt, nickel, chromium as an active ingredient may include cobalt, nickel, chromium as an impurity.

If in Eyes

• If dust is in eyes, immediately wash away with clean water (remove the contact lenses if possible). If irritation persists, get medical advice/attention.

If Swallowed

• If a large amount of dust is swallowed, get medical advice/attention after ingesting plenty of water to dilute.

5. Fire-Fighting Measures

Suitable Extinguishing Media and Unsuitable Extinguishing Media

• To extinguish the fire of dust, use dry sand, expanded vermiculite, dilatable perlite, ABC type (general, oil, electric fire) powder extinguishers or water (no water allowed for the dust containing cut powders of light metal such as magnesium and aluminum).

Special Protective Equipment and Emergency Procedures for Fire-Fighters

• In fighting a fire, wear a protective clothing, dust-proof respirator or respiratory protective equipment.

6. Accidental Release Measures

Personal Precautions, Protective Equipment, and Emergency Procedures

• It is recommended that someone who cleans dust should wear clothing and respiratory protective equipment to minimize exposure.

Environmental Precautions

• Dispose of dust as industrial wastes and prevent release in water systems.

Containment and Cleanup Methods and Equipment

• If there is dust which occur from Ceramic producing process, isolate the area and remove with a cleaner equipped with a filter which can take up fine particles very efficiently. If appropriate removing methods are not available, sweep with water sprayers or wet mops.

7. Handling and Storage

Handling

■ Technical Measures

- Ceramic is a stable substance and has little influence on health, but if it contacts dust or grinding liquid containing cobalt or nickel for a long time or repeatedly, rough skin may occur.
- If the disperse of dust containing cobalt or nickel is concerned, provide local exhaust ventilation and use personal protective equipment to minimize exposure to human body.

■ Precautions for Safe Handling

- Obtain safety instructions before use.
- Do not handle until all safety precautions have been read and understood.

■ Contact Avoidance

- Take measures described in "Exposure Controls/Personal Protection."
- Do not breathe dust, fume or vapor.
- Do not eat, drink or smoke in handling area.

■ Hygiene measures

- Wash skin thoroughly after handling.
- Do not release into the environment.

Storage

■ Conditions for Safe Storage

• Avoid sudden changes of temperature and high humidity for storage.

■ Materials for Safe Container

• Use materials meeting the specific gravity of Ceramic

8. Exposure Controls/Personal Protection

Exposure Prevention

• Permissible concentration in working environment (reference value)

| Ingredient | Chemical Formula | OSHA* PEL* mg/m³ | ACGIH* TLV* mg/m³ | Japan Society for Occupational Health Exposure Limit* mg/m ³ |
|------------------------|---|---------------------|----------------------|--|
| Aluminum oxide | Al_2O_3 | 5 (as Al) | 10 | N/A |
| Zirconium oxide | $ m ZrO_2$ | 5 (as Zr) | 5 (as Zr) | 0.5 (as Zr) |
| Titanium oxide | ${ m TiO_2}$ | 15 | 10 | N/A |
| Ytterbium oxide | Yb_2O_3 | N/A | N/A | N/A |
| Yttrium oxide | Y_2O_3 | 1 (as Y) | 1 (as Y) | N/A |
| Erbium oxide | $\mathrm{Er}_{2}\mathrm{O}_{3}$ | N/A | N/A | N/A |
| Magnesium oxide | MgO | 15 | 10 | N/A |
| Chromium oxide | $\mathrm{Cr_2O_3}$ | 0.5 (as Cr) | 0.5 (as Cr) | 0.5 (as Cr) |
| Cerium oxide | CeO_2 | N/A | N/A | N/A |
| Yttrium aluminum oxide | Y ₂ Al ₅ O ₃ | 1 (as Y) | 1 (as Y) | N/A |
| Silicon carbide | SiC | 5 | 3 | N/A |
| Aluminum nitride | AlN | 5 (as Al) | 1 (as Al) | N/A |
| Silicon nitride | $\mathrm{Si}_{3}\mathrm{N}_{4}$ | N/A | N/A | N/A |
| Titanium nitride | TiN | N/A | N/A | N/A |
| Cobalt | Co | 0.1 | 0.02 | 0.05 |
| Cobalt oxide | $\mathrm{Co_3O_4}$ | (as Co) | (as Co) | (as Co) |
| Nickel | Ni | 1.0 | 1.5 | 1.0 |
| Nickel oxide | NiO | (as Ni) | (as Ni) | (as Ni) |
| Tungsten Carbide | WC | 5 (as W) | 5 (as W) | N/A |
| Tantalum carbide | TaC | 5 (as Ta) | 5 (as Ta) | N/A |
| Niobium carbide | NbC | N/A | N/A | N/A |
| Titanium carbide | TiC | N/A | N/A | N/A |
| Titanium carbonitride | TiCN | N/A | N/A | N/A |

*OSHA: Occupational Safety & Health Administration U.S. Department

*PEL: Permissible Exposure Limit

*ACGIH: American Conference of Governmental Industrial Hygienists Inc.

*TLV: Threshold Limit Value

* Exposure If processing such as polishing and cutting that generates dust, for Limit: ingredients with not indicated value, refer to the exposure limit of the

Japan Society for Occupational Health

*N/A: Not Applicable

· Facility measures

Provide local exhaust ventilation so that dusts in the air may not exceed the exposure limits in the above table. It is to be noted that management concentration of the cobalt (and its inorganic compounds) is to be 0.02mg/m^3 in accordance with the working environment assessment standard by Japanese Minister of Health, Labour and Welfare under the paragraph (2), Article 65-2 of the Industrial Safety and Health Act in Japan.

In addition, cobalt (and its inorganic compounds) in the storage or handling, and that to take the necessary action conforming to the Ordinance on Prevention of Hazards due to Specified Chemical Substances.

Protection Measures

• Respiratory Protection: Dust-proof respirators and respiratory protective equipment are recommended.

• Hand Protection: Protective gloves for dust are recommended.

• Eye/Face Protection: Eye and face protections for dust are recommended.

• Skin/Body Protection: Avoid direct skin contact.

Clean up deposited dust on clothing, rags, etc. by washing or absorbing with suitable filters but not by whisking off.

Change the contaminated clothing into clean one.

Hygiene Measure

Wash skin thoroughly after handling.

9. Physical and Chemical Properties

Physical State: Solid state Color: Dark grey color

(in case of the coated or surface treated Ceramic, the appearance color

is often different.)

Odor: Odorless

Melting/Freezing No data available

Point:

Boiling or Initial No data available

Boiling Point and Boiling Range:

Flammability, No data available

Explosion Limits,

Flammability Limit, Flash

Point,

Spontaneous Ignition Temperature,

Resolution
Temperature:

pH: No data available Kinematic No data available

Viscosity:

Solubility: Insoluble

Vapor Pressure: No data available

Density and/or 11.0 - 15.5

Relative Density:

Relative Gas No data available

Density:

Particle No data available

Properties:

10. Stability and Reactivity

A grain of dust which occur from Ceramic producing process is very fine and under the specific conditions in which the dusts are mixed with grinding oil with low flash point, it is possible to become pyrophoric. If dusts under very flammable conditions are dispersed in the air, it is possible to explode.

The each metallic ingredients (cobalt, nickel and chromium) for composing the Ceramic has the following information about stability and reactivity under specific conditions.

Stability and reactivity of cobalt alone in below,

(When cobalt is included as ingredients of Ceramic.)

Reactivity, chemical stability: Stable to heat and contact with water

Ignite spontaneously in air

Hazardous reactions: It reacts with strong oxidizing agents

It reacts violently with oxygen, and it poses a risk

of fire or explosion

It reacts violently with acid to generate hydrogen

Conditions to avoid: Contact with incompatible materials

Incompatible materials: Strong oxidizing agents, acid

Hazardous decomposition products: By combustion, cobalt oxide and fumes of cobalt

oxide may occur

Stability and reactivity of nickel alone in below, (When nickel is included as ingredients of Ceramic.)

Reactivity, chemical stability: It is considered stable in storage and handling in

accordance with the laws and regulations

Hazardous reactions: Metallic nickel is usually stabilized against

oxidation by the oxide film, fresh metal surfaces without oxide film is rapidly oxidized by air. Thus, fresh metallic nickel powder, there is a risk of

ignition in air.

Conditions to avoid:

Hazardous decomposition products:

No data available

No data available

Stability and reactivity of chromium alone in below, (When chromium is included as ingredients of Ceramic.)

Reactivity, chemical stability: Stable under normal handling conditions

Hazardous reactions: Reacts violently with strong oxidizing agents such

as hydrogen peroxide, it poses a risk of fire or

explosion.

It reacts with dilute hydrochloric acid and dilute

sulfuric acid.

Conditions to avoid: The alkali or alkaline carbonate is Incompatible.

When mixed with air in powder or granular form,

there is a possibility of dust explosion.

Incompatible materials: Strong oxidizing agents, dilute hydrochloric acid,

dilute sulfuric acid, alkali, alkali carbonate

Hazardous decomposition products: During combustion, there can be irritating or toxic

fumes and gases.

11. Toxicological Information

Acute Toxicity:

No data available on Ceramic
Skin Corrosion/Irritation:
No data available on Ceramic
Serious Eye Damage/Eye Irritation:
No data available on Ceramic
Respiratory or Skin Sensitization:
No data available on Ceramic
No data available on Ceramic
No data available on Ceramic

Carcinogenicity: Group 2A on IARC, as cobalt powder

coexisting with tungsten carbide powder. Suspected to be carcinogenic in humans

(Ref. 1)

Reproductive Toxicity: No data available on Ceramic Specific Target Organ Toxicity/Systemic Toxicity: No data available on Ceramic

(Single Exposure)

Specific Target Organ Toxicity/Systemic Toxicity: No data available on Ceramic

(Repeated Exposure)

Aspiration Hazard: No data available on Ceramic

12. Ecological Information

Ecotoxicity, Persistence, Degradability, Bioaccumulation, Mobility in soil, Hazardous to the ozone layer

• No data available on Ceramic

13. Disposal Considerations

Safe and environmentally desirable disposal or recycle method

• For disposal, conform to the applicable laws regarding industrial wastes such as 'Waste Disposal and Public Cleansing Law' and relevant local by laws.

14. Transport Information

International Regulations

UN Number: Not applicable Proper Shipping Not applicable

Name

UN Hazard Class: Not applicable
Packing Group Not applicable
Marine Pollutant: Not applicable

Domestic Regulations

Land Regulatory Information In accordance with

the Fire Service Act/

the Road Act

Marine Transportation In accordance with

Information: the Ship Safety Act/ the Act on Port

the Act on Po Regulations

Marine Pollutant: Not applicable

Aviation transportation In accordance with information: the Civil Aeronautics

Act

Special Safety Measures for Transportation and Transportation Method

When transporting the dust which occur from Ceramic producing process, make sure that there is no damage or corrosion or leakage of the container, to ensure implementation of the prevention of collapse of cargo.

15. Regulatory Information

Name and Information of Applicable Regulatory

• Law for Pollutant Release and Transfer Register (PRTR)

Cobalt: "Class 1 designated chemical substances", Cabinet Order No.132
Cobalt oxide: "Class 1 designated chemical substances", Cabinet Order No.132
Nickel: "Class 1 designated chemical substances", Cabinet OrderNo.308
Nickel oxide: "Class 1 designated chemical substances", Cabinet OrderNo.309
Chromium oxide: "Class 1 designated chemical substances", Cabinet OrderNo.87

^{*}When transporting a powder of metallic ingredients (cobalt, nickel) for composing the Ceramic, there is a possibility that it is necessary to take appropriate action in accordance with the relevant provisions established by IMO (International Maritime Organization), ICAO (International Civil Aviation Organization), IATA (International Air Transport Association).

^{*}When transporting a powder of metallic ingredients (cobalt, nickel) for composing the Ceramic, there is a possibility that it is necessary to take appropriate action in accordance with the relevant provisions of Ship Safety Law and the Aviation Law.

- Industrial Safety and Health Law, Ordinance on Prevention of Hazards due to Specified Chemical Substances
- Aluminum oxide: The substances are defined in the Article 57-2 of the Act, and the aluminum oxide is listed by No.189 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."
- Zirconium oxide: The substances are defined in the Article 57-2 of the Act, and the zirconium oxide is listed by No.313 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."
- Titanium oxide: The substances are defined in the Article 57-2 of the Act, and the titanium oxide is listed by No.191 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."
- Yttrium oxide: The substances are defined in the Article 57-2 of the Act, and the yttrium oxide is listed by No.54 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."
- Chromium oxide: The substances are defined in the Article 57-2 of the Act, and the chromium oxide is listed by No.142 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."
- Silicon carbide: The substances are defined in the Article 57-2 of the Act, and the silicon carbide is listed by No.336 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."
- Cobalt/Cobalt oxide: The substances are defined in the Article 57-2 of the Act, and the cobalt/cobalt oxide is listed by No.172 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."

 Article 2, Paragraph 1, Items 2 and 5 of Ordinance on Prevention of Hazards due to Specified Chemical Substance, Specified chemical substance class 2, Management class 2.

 When the content of cobalt and cobalt oxide is less than 1%, the Ordinance on Prevention of Hazards due to Specified Chemical Substance is not covered.
- Nickel/Nickel oxide: The substances are defined in the Article 57-2 of the Act, and the nickel/nickel oxide is listed by No.418 in Appended Table9 in the Article 18-2 of the Enforcement Order as "Dangerous or Harmful Substances to be notified their names, etc."

16. Other Information

Other Hazardous Information

The following attention should be paid for dust which occur from Ceramic producing process.

- If a large amount of dust containing cobalt is inhaled, blood, heart, thyroid gland, and spleen disorders may result. (Ref.2)
- It is reported that repeated or prolonged contact with cobalt, nickel, nickel oxide, chromium or zirconium oxide may affect skin, respiratory organs, heart, etc. (Ref.3 6)
- Inhaling high concentration dust of aluminum oxide may irritate the eyes and upper respiratory tract. (Ref.4)
- Repeated or prolonged inhalation and exposure of aluminum oxide may cause effects on

- the central nervous system. (Ref.4)
- Zirconium oxide can cause dizziness, increased perspiration, decreased capillary resistance, increased temperature sensation and pain sensation, skin granulomas, irritating symptoms of mild respiratory organs. (Ref.5)
- Magnesium oxide irritates the eyes and nose. Also, inhaling fumes may cause metal heat. (Ref.4)
- For carcinogenicity of metallic ingredients of cemented carbide has the following knowledge.

| Cobalt metal | ACGIH | A3: Confirmed animal carcinogen with |
|----------------|-------------------|--|
| | | unknown relevance to humans. |
| | IARC | 2B: Possibly carcinogenic to humans. |
| | Japan Society for | 2B: The substance has been determined to be |
| | Occupational | possibly carcinogenic to humans (with |
| | Health | relatively insufficient evidence). |
| Nickel metal | ACGIH | A5: Not suspected as a human carcinogen. |
| | IARC | 2B: Possibly carcinogenic to humans. |
| | Japan Society for | 2B: The substance has been determined to be |
| | Occupational | possibly carcinogenic to humans (with |
| | Health | relatively insufficient evidence). |
| Nickel oxide | ACGIH | A1: Confirmed carcinogenic to humans. |
| | IARC | 1: Proof to be carcinogenic to humans |
| | Japan Society for | 2B: The substance has been determined to be |
| | Occupational | possibly carcinogenic to humans (with |
| | Health | relatively insufficient evidence). |
| Chromium metal | IARC | 3: Not classifiable as to its carcinogenicity to |
| | | humans. |
| Ceramic fiber | IARC | 2B: Possibly carcinogenic to humans. |
| (Whisker) | | |
| | | |

*ACGIH: American Conference of Governmental Industrial Hygienists Inc.

*IARC: International Agency for Research on Cancer

Disclaimer

The contents of this SDS are based on material and information available as of today and may be revised due to knowledge newly obtained. The values of concentration, physical/chemical properties are not guaranteed. In addition, the precautions described herein apply only to normal uses, and thus safety cannot be guaranteed.

Reference URL

Ministry of Economy, Trade and Industry: http://www.meti.go.jp/
 Ministry of the Environment: http://www.env.go.jp/
 Ministry of Health, Labour and Welfare: http://www.mhlw.go.jp/
 Japan Industrial Safety and Health Assoc.: http://www.jaish.gr.jp/
 International Agency for Research on Cancer: http://monographs.iarc.fr/
 International Chemical Safety Card: http://www.nihs.go.jp/ICSC/

• National Institute of Technology and Evaluation:

http://www.safe.nite.go.jp/ghs/list.html

Reference Documents

- (1) IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, vol.86 (2006).
- (2) Food & Drug Research Laboratories, study No.8005B (4.11.84).

- (3) T. Shirakawa et al., Chest. 95, 29 (1989).
- (4) International Chemical Safety Cards (cobalt, chromium, nickel).
- (5) The Guide to Chemical Hazards (edited by Japan Industrial Safety & Health Association)
- (6) A. O. Bech et al., Brit. J. Ind., 19, 239 (1962).